

Instrumentation & Piping valves





Monoflange valves









Plug valves

Large bore ball valves

Injection & sampling valves







Various instrumentation valves

For more than 20 years **Imperial Valve** has been successfully supplying instrument needle valves, ball valves and manifolds to the oil, gas and petrochemical industries.



Needle valves and manifolds Ball valves FLOW DIAGRAM

Features

- Material traceability EN10204-3.1 standard
- Non-rotating stem
- Anti-blow out stem
- Optional handle locking
- Low operating torque on high pressures

- Ratings: 6,000 PSI & 10,000 PSI
- Sizes: 1/4"-1"
- Materials: a wide selection of materials for both body and internals, e.g.: carbon steel, low alloy steels, stainless steels, Duplex, Ni-alloys and titanium. Incuding NACE MR-01-75 (latest revision)



Medium and high pressure valves

With the increasing demand of the market for high pressure valves, **Imperial Valve** has responded with an extended range of medium pressure (ca. 20,000 psi) and high pressure (up to 60,000 psi) needle and ball valves.




Needle valves medium & high pressure









Ball valves medium & high pressure

Features

- Adjustable packing for high cycle life and low operating torque
- Blow out resistant 2-piece non rotating stem with stem bearing for high cycle life and low torque operation
- Three standard mounting options
- Large section of tube and pipe fittings available
- Optional valve locking
- Easy panel mounting
- Ball valves: floating ball or trunnion mounted available

Specifications

- Sizes: 1/4"-1"
- Ratings: 10,000 PSI, 20,000 PSI and 60,000 PSI
- Materials: a wide selection of materials for both body and internals, e.g.: carbon steel, low alloy steels, stainless steels, Duplex, Ni-alloys and titanium. Incuding NACE MR-01-75 (latest revision)



FLOW DIAGRAM

Monoflange valves

Where compactness and a high specification for mechanical and piping applications is required, **Imperial Valve** offers a complete range of monoflange valves in accordance with ANSI / ASME B.16.34.



Block valves






Monoflange double block & bleed valves







Features

- Fully in accordance with ANSI / ASME specifications
- Fire safe tested in accordance with BS 6755 part II
- Fully integral (OS+Y) bolted bonnet
- Metal seated on high pressure gas applications
- Saving space, weight and money

- All ANSI / DIN flange sizes available
- Ratings: ANSI 150 2500 LBS / DIN PN10-PN160
- Materials: a wide selection of materials for both body and internals, e.g.: carbon steel, low alloy steels, stainless steels, Duplex, Ni-alloys and titanium. Incuding NACE MR-01-75 (latest revision)



Where compactness and a high specification for mechanical and piping applications is required, **Imperial Valve** offers a complete range of instrument double block & bleed valves in accordance with ANSI / ASME B.16.34.





FLOW DIAGRAM



Features

- Through bore ball-needle-ball configuration
- Reduced and full bore sizes available
- Flange x thread or flange x flange configurations
- Sampling and chemical injection versions available
- Handle locking option available
- Fire tested in accordance with BS6755 part II

- Flange sizes 1/2" upto 3"available
- Ratings: ANSI 150-2500 lbs / DIN PN10-PN160
- Materials: a wide selection of materials for both body and internals, e.g.: carbon steel, low alloy steels, stainless steels, Duplex, Ni-alloys and titanium. Incuding NACE MR-01-75 (latest revision)




Imperial Valve has introduced a new selection of large bore ball valves, including double block & bleed valves. These valves are available with ANSI and DIN flanges, sizes 1"-24", rating 150-2500 lbs / PN10-PN160, floating ball or trunnion mounted.



Single block ball valves






Double block & bleed valves







Features

- Floating ball or trunnion mounted ball
- Actuators, gear boxes and extended handles can be offered for these valves
- Cryogenic and high-temperature applications are available
- Soft or metal seated

- Sizes: 2"-24"; ANSI and DIN flange
- Ratings: ANSI 150-2500 lbs / DIN PN10-PN160
- Materials: a wide selection of materials for both body and internals, e.g.: carbon steel, low alloy steels, stainless steels, Duplex, Nialloys and titanium. Incuding NACE MR-01-75 (latest revision)



Imperial Valve has introduced a new selection of large bore plug valves including double isolating plug valves. These valves are available with ANSI and DIN flanges, sizes 1"-24", rating 150-2500 lbs / PN10-PN160.



Lubricated plug valves








Double isolating plug valves







Features

- Re-adjustable packing / plug
- Actuators, gear boxes and extended handles can be offered for these valves
- High-temperature applications available
- Lubricated metal seated or soft seated
- 3-way plug valves availabe

- Sizes: 2"-24"; ANSI and DIN flange possible
- Ratings: ANSI 150-2500 lbs / DIN PN10-PN160
- Materials: a wide selection of materials for both body and internals, e.g.: carbon steel, low alloy steels, stainless steels, Duplex, Ni-alloys and titanium. Incuding NACE MR-01-75 (latest revision)



Turn key solutions

Working together with major operators in the field of oil, gas and power generation, **Imperial Valve** has produced many turn-key solutions over three decades. Some of them are high lighted below.





Features

- Integral solutions often reduce the number of potential leak paths making a safer system
- By reducing the size and weight of hook-ups,
 these solutions will make considerable financial savings

Specifications


 All solutions are in accordance with the relevant international standard and specifications



Instrument enclosures

Together with DP Systems, **Imperial Valve** can offer a complete range of Glass Reinforced Polyester (GRP) instrument enclosures for protection against frost, sand, salt spray and other harmful environments.







Non-rigid enclosures





Features

- Diagonal split/front door type available
- Thermally insulated body enclosures available
- Standard colour light gray
 Other colours available
- Stainless steel toggles and fasteners

- Protection rating to IP66, BS 5490 / IEC 524
- Temperature range -55°C to +140°C
- Impact resistant to BS 5501
- Fire retardant to BS 476 part 7 class 2 and self extinguishing
- Anti-static to BS 5501 available



Check valves & accessories

Imperial Valve offers a new range of in-line instrument check valves in 6,000 and 10,000 PSI rating. To assure correct fit of valuable instruments we also provide a wide range of accessories.







Features

- Compact design in-line instrument check valves prevents back flow
- Imperial Valve instrument accessories are designed with very close tolerances and high mechanical quality to assure perfect fit with your valuable instruments

- Check valves, in-line, 6,000 and 10,000 PSI, size range 1/4"-1"
- Standard cracking pressure is 20 PSI (1,38 bar) ± 30%
- Wide range of materials available







Imperial Valve BV, the Netherlands

- Sales office
- Production
- Assemblies / Turn key projects
- Testing & inspection
- Warehouse



Information and sales offices Imperial Valve:

• Regional sales representative:

• The Netherlands:

ITE De Gidts & Feldman BV

Telephone: +31 (0)36 531 40 14 Fax: +31 (0)36 531 36 84 E-mail: salesdept@dgfg.nl Postal address: P.O. Box 50041,

1305 AA Almere, the Netherlands

Website: www.dgfg.nl

• Outside the Netherlands / Worldwide:

Imperial Valve BV

Telephone: +31 (0)36 531 40 14 Fax: +31 (0)36 531 36 84 E-mail: salesdept@imperialvalve.nl

Postal address: P.O. Box 50041,

1305 AA Almere, the Netherlands

Website: www.imperialvalve.nl

Disclaimer: This brochure has been prepared by Imperial Valve BV, the Netherlands. This brochure is a guide only. Whilst all information has been gathered from sources we deem to be reliable, we do not guarantee the accuracy of this information. Text may change at any time, without notice. The shown pictures may be different from supplied goods.